

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>B01F 17/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/67017</b> <b>(43) International Publication Date:</b> 29 December 1999 (29.12.99)
<b>(21) International Application Number:</b> PCT/US99/14072 <b>(22) International Filing Date:</b> 22 June 1999 (22.06.99) <b>(30) Priority Data:</b> 60/090,324 23 June 1998 (23.06.98) US <b>(71) Applicant (for all designated States except US):</b> UNION CARBIDE CHEMICALS & PLASTICS TECHNOLOGY CORPORATION [US/US]; 39 Old Ridgebury Road, Danbury, CT 06817-0001 (US). <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> POLOVSKY, Stuart, Barry [US/US]; 8 Crabtree Road, Matawan, NJ 07747 (US). BARBEITO, Carmella [US/US]; 1 Hemlock Drive, Edison, NJ 08820 (US). LI, Wing, Kin [US/US]; 21 Berkshire Way, New Brunswick, NJ 08816 (US). DiANTONIO, Edward, F. [US/US]; 269 Granite Avenue, Staten Island, NY 10303 (US). KREEGER, Russell, Lowell [US/US]; 4 Cornfield Terrace, Flemington, NJ 08822 (US). <b>(74) Agent:</b> WIGGINS, Karen, Johnson; Union Carbide Chemicals & Plastics, Technology Corporation, 39 Old Ridgebury Road, Danbury, CT 06817-0001 (US).		<b>(81) Designated States:</b> AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GE, HU, ID, IL, IS, JP, KR, KZ, LC, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, RU, SG, SI, SK, TR, TT, UA, US, UZ, VN, ZA, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
<b>(54) Title:</b> LIQUID THICKENER FOR SURFACTANT SYSTEMS		
<b>(57) Abstract</b>  Compositions comprising alkoxylated lipophilic polyol compounds, e.g., ethoxylated, esterified methyl glucosides, are disclosed wherein at least 5 % of the polyol derivatives have about three moles of the lipophilic substituent per mole of polyol. Quite advantageously, the disclosed polyol derivatives can be dissolved into aqueous solutions to provide liquid thickeners suitable for thickening surfactant-containing compositions, e.g., shampoos, at cold processing temperatures.		

*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Larvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## **LIQUID THICKENER FOR SURFACTANT SYSTEMS**

### **Field of the Invention**

The present invention relates to alkoxyated, lipophilic polyol compounds having about three moles of lipophilic substituents per mole of polyol and, more specifically, to the use of such compounds as thickeners in liquid surfactant compositions.

### **Background of the Invention**

Liquid compositions containing surfactants, e.g., shampoos, dishwashing liquids and other personal care and industrial products, typically contain thickeners in order to viscosify the liquid compositions sufficiently to enable convenient handling. Often, the thickeners comprise an alkoxyated polyol containing lipophilic substituents, e.g., ethoxylated methyl glucose esterified with a fatty acid. Such thickeners are typically alkoxyated to an extent sufficient to provide water-solubility and provide viscosification to the liquid surfactant composition. The lipophilic substituent, e.g., fatty acid, typically provides associative thickening characteristics to the thickener.

Often, the thickeners are introduced to the liquid surfactant compositions in solid form and mixed under conditions effective to dissolve the thickener into the liquid surfactant composition and cause significant viscosity increases, e.g., up to about 2,000 to 100,000 centipoise ("cP") or higher. Frequently, the mixing must be conducted at elevated temperatures, e.g., from about 50 to 80°C, in order to promote the dissolution of the thickener and obtain the desired viscosity enhancement (known in the art as "hot processing"). However, formulators of products comprising thickened, surfactant-containing liquids, e.g., shampoos, desire the ability to formulate their

- 2 -

products at ambient temperatures, e.g., from about 20 to 30°C (known in the art as "cold processing"). Additionally, formulators also desire thickeners which can be introduced to the liquid surfactant compositions in a liquid form rather than a solid form. The ability to introduce the thickener in a liquid form can provide a formulator with a greater degree of accuracy in introducing the correct amount of thickener to the liquid surfactant system and also better facilitate automated processing.

Accordingly, improved compositions suitable for use as thickeners in liquid surfactant systems are desired. Preferably, the thickeners can be introduced by cold processing and in a liquid state. Methods for using the compositions to thicken liquid compositions comprising surfactants are also desired.

### Summary of the Invention

By the present invention, alkoxyated, lipophilic polyol compounds, e.g., ethoxylated, esterified methyl glucosides, are provided which are useful, for example, as thickeners in liquid surfactant-containing systems. In the compositions of the present invention, at least 5 wt. % of the polyol compounds have about three moles of the lipophilic substituent per mole of polyol. Quite surprisingly, it has been found in accordance with the present invention that the presence of a sufficient portion of the polyol compounds having about three moles of the lipophilic substituent per mole of the polyol can enhance the ability of the composition to thicken a liquid surfactant system, preferably at cold processing temperatures.

In addition, the present invention provides processes for preparing the compositions which include the steps of alkoxyating the polyol with a suitable alkoxylation reagent, e.g., ethylene oxide, and introducing a lipophilic substituent, e.g., by esterification with a fatty

acid. The processes also provide for introducing the lipophilic substituents prior to the alkoxylation step as well as sequential introductions of the lipophilic substituent and the alkoxyating reagent.

### **Detailed Description of the Invention**

The polyols suitable for use as starting materials in accordance with the present invention comprise any compounds having three or more hydroxyl groups per molecule which are reactive with the alkoxylation reagents and the lipophilic reagents described below. General examples include glycerols, polyglycerols, sugar alcohols, e.g., sorbitol or sorbitan, and saccharides, e.g., glucose and its derivatives. More specific examples of the polyols which can be used according to the invention include, but are not limited to, trimethylolethane [2-methyl-2-(hydroxymethyl)-1,3-propanediol], trimethylolpropane[2-ethyl-2-(hydroxymethyl)-1,3-propanediol], pentaerythritol (2,2-dimethylol-1,3-propanediol), diglycerol (glycerol dimer), dipentaerythritol, glycerol, and the like.

Preferred polyol starting materials for use in accordance with the present invention are glucose derivatives, more preferably, glycosides, e.g., glucosides, galactosides, monosaccharides, oligosaccharides having up to about 10 saccharide repeat units per molecule and sucrose. Especially preferred glucosides include alkyl glucosides, such as for example, methyl glucoside, ethyl glucoside, propyl glucoside, butyl glucoside and amyl glucoside.

Such polyols are commercially available.

Suitable reagents for alkoxyating the polyols are alkylene oxides, such as, for example, ethylene oxide, propylene oxide, butylene oxide and mixtures thereof. Other alkoxyating reagents, e.g., higher alkylene oxides, may be used in accordance with the present invention.

Alkylene oxides suitable for use in accordance with the present invention are commercially available. The amount of alkoxylation in accordance with the present invention is that which is effective to provide water solubility and viscosification in a liquid surfactant composition. Typically, such amounts range from about 50 to 400, preferably from about 80 to 180 and more preferably from about 100 to 160 moles of alkylene oxide per mole of polyol. Methods for alkoxyating polyols, e.g. by direct alkoxylation, are known to those skilled in the art. Alternatively, partially alkoxyated methyl glucosides, e.g., GLUCAM™ E-20 (PEG-20 methyl glucoside) available from Amerchol Corporation, Edison, NJ, can be used as a starting material which can then be further alkoxyated to contain the desired degree of alkoxylation.

The lipophilic reagents suitable to derivatize the polyols of the present invention include any compounds which are reactive with the polyols and have sufficient molecular weight to promote associative thickening when introduced into a liquid, surfactant-containing system. Typically, the lipophilic reagents comprise hydrocarbon or substituted hydrocarbon moieties with from about 8 to 30, preferably from about 12 to 26 and more preferably from about 16 to 22 carbon atoms per molecule. The particular structure of the lipophilic reagents is not critical to the present invention and may, for example, be alkyl, aryl, alkylaryl, alkenyl and may be cyclic, branched or straight. Typically, the reagents are fatty acids, fatty esters, epoxides, halides glycidyl ethers, or vegetable or animal oils. The reagents typically provide either an ester or ether linkage to the polyol. Stated another way, in the case of a glucose derivative, for example, the ether or ester is typically attached to the glucose derivative indirectly through a polyoxyalkylene chain.

Examples of suitable fatty acids include natural or synthetic saturated or unsaturated acids which are linear or branched. The fatty acids can be used alone or as a mixture. Natural fatty acids include, for example, saturated or unsaturated linear fatty acids such as caproic acid, enanthic acid, caprylic acid, pelargonic acid, decanoic acid, lauric acid, myristic acid, palmitic acid, stearic acid, linolic acid, oleic acid, capric acid and undecanoic acid which are typically obtained by hydrolyzing vegetable oils and animal oils such as coconuts oils, palm oil, tallow, linseed oil and soybean oil. Examples of synthetic fatty acids, include linear or branched fatty acids prepared by oxidizing olefin polymers. It is also possible to use fatty acids derived from microorganisms such as, for example,  $\gamma$ -linolenic acid. Further, as the lower alkyl ester of the fatty acid, alkyl esters having 1 to 8 carbon atoms such as methyl, ethyl or propyl ester of the fatty acid described above can be used. The fatty acid esters of hexose or the alkyl glycoside thereof can be synthesized by using various known methods, including ester synthesis using lipase and the like: for example; (1) an ester exchange reaction between starting oils or fats and a hexose or its alkylglycoside, (2) an ester exchange reaction between a lower alkyl ester of a fatty acid and a hexose or its alkyl glycoside, or (3) an ester synthesis between a fatty acid and a hexose or its alkyl glycoside. In addition, a synthesis process using a fatty acid chloride and a hexose or its alkyl glycoside may also be employed.

Examples of other suitable lipophilic reagents include glycidyl ethers, e.g., nonylphenylglycidyl ether or dodecylphenyl glycidyl ether, alpha-olefin epoxides, e.g., 1,2-epoxyhexadecane and their respective chlorohydrins, or alkyl halides, e.g., dodecylbromide, and the above-mentioned vegetable and animal oils. Halogenated products of fatty acids can also be used as the lipophilic reagent.

The amount of the lipophilic reagent used to derivatize the polyols of the present invention is preferably effective to promote associative thickening behavior of the polyol derivatives when present in a liquid surfactant composition. Typically, the average substitution level of the lipophilic substituent is about 3, e.g., from 2.5 to 4, preferably from about 2.5 to 3.9 and more preferably from about 2.8 to 3.6, moles per mole of polyol. Details concerning the derivatization of polyols to comprise lipophilic substituents are known to those skilled in the art. The average amount of lipophilic substituent per mole of polyol (referred to in the art as Degree of Substitution "DS") can be determined by any technique known to those skilled in the art, e.g., by nuclear magnetic resonance spectroscopy ("NMR"). The lipophilic reagents suitable for use in accordance with the present invention are commercially available.

In accordance with the present invention, the alkoxyated, lipophilic polyol compounds comprise a mixture of compounds substituted with varying amounts of the lipophilic substituent depending upon the available hydroxyl groups on the polyol starting material. At least 5% of the polyol compounds in the composition have about three moles of the lipophilic substituent per mole of polyol. For example, in the case of an ethoxylated, esterified methyl glucoside, at least 5% of the compounds are substituted with about three moles of the lipophilic substituent per mole of the methyl glucoside. Typically, at least 25%, preferably at least 50% and more preferably at least 75% of the polyol derivatives in the composition have about three moles of the lipophilic substituent per mole of polyol. Typically, the balance of the composition comprises polyol derivatives having one, two or four moles of the lipophilic substituent per mole of polyol. Typically, less than about 75%, preferably less than about 50% and more preferably



less than about 25% of the polyols in the composition comprise one, two or four moles of the lipophilic substituent per mole of polyol.

The sequence in which the alkylene oxide and lipophilic substituents are reacted onto the polyol is not critical to the present invention. In one aspect of the invention, the alkoxylation reaction is conducted first, followed by substitution of the lipophilic substituent onto the polyol. In another aspect of the invention, the polyol is first substituted with the lipophilic substituent followed by alkoxylation. In still yet another aspect of the invention, the polyol is partially esterified, e.g., to comprise one or two moles (on average) of the lipophilic substituent per mole of polyol, then ethoxylated, then subsequently esterified, e.g., to comprise about three moles of the lipophilic substituent per mole of polyol. Alternatively, the polyol can be partially ethoxylated, esterified and then ethoxylated again to the desired level. Moreover, the starting material can be the polyol, a partially alkoxyated polyol or a polyol that is partially reacted with the lipophilic reagent, or both.

The derivatizations are typically conducted under subatmospheric pressure, e.g., from about 0.001 to 1.0 atmospheres, and at a temperature in the range of about 110 to 180°C for the alkoxylation step and about 120 to 200 °C for the lipophilic substitution step. Catalysts may or may not be used for the derivatizations. Typically, however, catalysts are employed to enhance the reaction rate. The catalysts can be acidic, basic, or neutral. Preferred catalysts for the alkoxylation step include Na, NaOCH<sub>3</sub>, KOH, NaOH, K<sub>2</sub>CO<sub>3</sub>, Na<sub>2</sub>CO<sub>3</sub>. Preferred catalysts for the lipophilic substitution step include Na<sub>2</sub>CO<sub>3</sub>, KOH, NaOH, acids including p-toluenesulfonic acid ("p-TSA"), H<sub>2</sub>SO<sub>4</sub>, HCl, and others including organic titanates, e.g., tetraisopropyl titanate available as Tyzor™

catalyst from DuPont Company, Wilmington, DE. Further details concerning the manufacture of alkoxyated, lipophilic polyol compounds are known to those skilled in the art and are described, for example, in U.S. Patent Nos. 4,687,843, 5,109,127, 5,501,813 and 5,502,175.

The product produced from the derivatization reactions is typically in the form of a solid in a granulated or powdered form. The solid product is suitable for packaging and shipment to customers.

In a preferred aspect of the invention, the alkoxyated, lipophilic polyol derivatives are dissolved in a suitable solvent to provide a liquid thickener suitable for use in viscosifying surfactant-containing liquid compositions. Any suitable liquids capable of dissolving the polyol derivatives are suitable for use in accordance with the present invention. Preferably, the liquids are aqueous with or without additional water miscible liquids. For example, suitable solvents include alkylene glycols having about 2 to 5 carbon atoms per molecule, such as propylene glycol, ethylene glycol, butylene glycol, propane diol and butane diol. Other solvents, such as for example, polyalkylene glycols, e.g., CARBOWAX™ PEG and UCON™ Fluids available from Union Carbide Corporation, Danbury, CT, may also be employed. When the product is provided in a liquid form, it typically comprises from about 20 to 60 preferably from about 30 to 50 of the polyol derivative with the balance comprising the liquid solvent and any desired additives, such as, for example, preservatives, biocides, etc., which are generally present in minor amounts, e.g. less than about 5 wt % based on the total weight of the liquid composition. In addition, when in liquid form it is preferred that the liquid containing the thickener has a viscosity which is low enough to permit the liquid to be pumped or poured without difficulty. Typically, the viscosity is less than about 6,000 cP, preferably less than about 4,000 cP. As used

herein, the term viscosity means the viscosity measured with a Brookfield Viscometer with a suitable spindle and rotational speed as determined by one skilled in the art, e.g., spindle 6 to 10 rpm.

In one preferred aspect of the invention when the polyol is a glucose derivative, the liquid composition comprises from about 10 to 30 wt % water, from about 30 to 50 wt % propylene glycol and from about 30 to 50 wt % of the glucose derivative. An especially preferred composition comprises about 20 wt % water, about 40 wt % propylene glycol and about 40 wt % of the glucose derivative.

The alkoxyated, lipophilic polyol derivatives of the present invention have a variety of end used applications, such as, for example, personal care applications and industrial applications. Typical personal care applications include, for example, pharmaceutical and cosmetic compositions, such as, for example, shampoos, conditioners, ointments, skin creams, lotions, soaps, and the like. Typical industrial applications include, for example, use as viscosity adjusters for general fluids handling and for surfactant applications, such as, dishwashing liquids, laundry detergents, suspension aids, as adhesion promoters and coating materials.

In one aspect of the invention, the alkoxyated lipophilic polyol derivatives are used for thickening liquid compositions comprising one or more surfactants. Illustrative surfactants may include: anionics including fatty acid soaps, alkyl sulfates, alkyl ether sulfates, alkyl or aryl sulfonates, sulfosuccinates, sarcosinates, alkyl glucose esters or their alkoxyates and in particular sodium lauryl sulfate, ammonium lauryl sulfate, triethanolamine lauryl sulfate, sodium laureth sulfate, alpha olefin sulfonate, disodium laureth sulfosuccinates, triethanolamine stearate; nonionics including methyl glucose esters or their alkoxyates, fatty acid alkanol amides, polyglycol ethers or their alkyl or aryl derivatives, hydroxylated lanolin, lanolin alcohols and in

particular oleth-20, cetareth-20, methyl glucose dioleate, methyl glucose stearate, glycerol monostearate, cocoyl diethanolamide, nonoxynal-7 and octoxynol-8; cationics including alkyl trimethyl ammonium salts, quaternized amides of ethylene diamine, alkyl pyridinium salts and in particular cetrimonium chloride, stearalkonium chloride and cetyl pyridinium chloride; and amphoterics including alkyl  $\beta$ -aminopropionates, betaines, alkyl imidazolines and in particular cocoamphocarboxy glycinate, cocamidopropyl betaine and caproamphocarboxy propionate.

In this aspect of the invention, a first liquid comprising the alkoxyated, lipophilic polyol compounds, is combined with a second liquid comprising a surfactant under mixing conditions, in order to provide a viscosity enhancement of at least 10%, preferably at least 50%, more preferably at least 100% and most preferably at least 200%. As used herein, the term "Viscosity Enhancement" means the enhancement in viscosity, expressed as a percentage, in a surfactant-containing liquid composition between alkoxyated, lipophilic polyol compounds of the present invention compared to alkoxyated, lipophilic polyol compounds wherein a substantial fraction, e.g., at least 90%, of the compounds have about two moles, i.e., 1.5 to 2.5 moles, of lipophilic substituent per mole of polyol. For the measurement of Viscosity Enhancement, the mixing of the surfactant system is conducted at a temperature sufficient to dissolve the components, e.g., from ambient to about 80°C, with adequate mixing (preferably with no foaming) for about 2 to 3 hours. For determining Viscosity Enhancement, the alkoxyated, lipophilic polyol is utilized in the liquid surfactant composition at an active concentration of from about 0.1 to 5 wt %, preferably from about 0.1 to 1 wt %, based on the total weight of the liquid surfactant composition. For comparison purposes, the active concentration should be essentially the same. For this measurement a

- 11 -

Brookfield RVT viscometer with a No. 6 spindle at 10 rpm is generally suitable. The viscosity measurement should be taken at a fixed temperature, e.g., 22.5°C. Also, the comparison should be made using polyol derivatives having similar alkylene oxide substitution levels, e.g., within  $\pm 30$  alkylene oxide units, and a similar lipophilic substituent, e.g., within  $\pm 2$  carbon atoms per molecule.

A preferred surfactant composition for determining the Viscosity Enhancement comprises the following ingredients combined as described below.

Ingredients	wt%
Deionized Water	QS to 100
Sodium Laureth Sulfate -2(26 wt% active)	40.00
Cocamidopropyl Betaine (35 wt% active)	11.50
DMDM Hydantoin	0.4
Thickener(40 wt% polyol compound, 40 wt% propylene glycol, 20 wt% water)	1.25

**Procedure:** Add Sodium Laureth Sulfate -2 and Cocamidopropyl Betaine to the water in order, one at a time, until completely uniform before adding the next ingredient. Once uniform add the thickener with stirring and heat to 70°C. Once the thickener is totally dissolved start cooling system to 40°C. At 40°C add DMDM Hydantoin and continue to cool to room temperature. Record viscosity after 24 hours.

Quite advantageously, it has been found in accordance with the present invention that personal care products, e.g., shampoos, skin

- 12 -

creams and the like, may provide the following desirable characteristics. In the case of shampoos and other hair care products; improved rinseability, feel, lathering, combing potential, synergy with other ingredients, clarity and salt tolerance may be obtained. In the case of skin care products; improved anti-irritation properties, fattening agents, moisturization and dermatological compatibility may be obtained.

A typical cleansing formulation for skin or hair comprising the alkoxyated, lipophilic polyol compounds of the present invention may contain the following ingredients and can be prepared as described below.

<u>Ingredients</u>	<u>wt%</u>
Deionized Water	QS
Polyquaternium-10	0.20
Sodium Laureth Sulfate (26wt% active)	40.00
Cocamidopropyl Betaine (35wt% active)	11.50
Disodium Laureth Sulfosuccinate (40wt% active)	5.00
Thickener (40 wt% polyol compound, 40 wt% propylene glycol, 20 wt% water)	0.50
DMDM Hydantoin	0.40

**Procedure:** Add Polyquaternium-10 to room temperature deionized water with adequate agitation. When uniform heat to 70°C and mix until fully hydrated. Once fully hydrated add the remaining ingredients up until DMDM Hydantoin, one at a time in order, waiting

- 13 -

until for each to be dissolved before adding the next. Allow to cool to 40°C. At 40°C add DMDM Hydantoin. Continue to cool to room temperature.

### **EXAMPLES**

The following examples are provided for illustrative purposes and are not intended to limit the scope of the claims which follow. In the examples, the amounts recited are given in weight percent unless otherwise indicated.

#### **EXAMPLE 1 (Comparative)**

##### **PREPARATION OF PEG-120 METHYL GLUCOSE DIOLEATE-PG-WATER BLEND**

A sample of PEG-120 Methyl Glucose Dioleate (available from Amerchol Corporation, Edison, NJ, under the tradename Glucamate™ DOE-120) of 1000 grams ("gm") was placed in a flask equipped for agitation and heating. To this was added 1000 gm of propylene glycol and 500 gm of water. The mixture was heated to 60°C with stirring. Upon melting and continued agitation, the solids dissolved and the solution become fluid and transparent.

The final liquid product was then allowed to cool to room temperature. The product had a viscosity of <2000 cP at room temperature.

#### **EXAMPLE 2**

##### **PREPARATION OF PEG-100 METHYL GLUCOSIDE TRIOLEATE-PG-WATER BLEND**

Into a one liter pressure reactor, 192 gm of PEG-20 methyl glucoside (Glucam™ E-20, available from Amerchol Corporation,

Edison, NJ) was poured. To this was added 1 gm of KOH flakes. The vessel was closed and vacuum was increased as the temperature was increased to 140°C. The material was stirred and dried at 140°C and about 10mm Hg for 0.5 hrs.

The system was purged three times with nitrogen and pressurized to 25 psig. The liquid was ethoxylated with 630 gm of ethylene oxide at 140-145°C and 65 psig. After addition was completed, the reaction mixture was digested for one hour and purged with nitrogen to remove any residual oxide. This gave a hard white waxy material at room temperature of polyoxyethylene-100 methyl glucoside.

A sample of the above PEG-100 methyl glucoside (476 gm) was placed in a flask and warmed to about 50°C until all material melted. Oxalic acid (4.4 gm) was added in a small quantity of water. The mixture was stirred for about 0.5 hrs. and then dried under vacuum i.e., about 10 millimeters of mercury ("mm Hg") at 110°C.

Vacuum was broken with nitrogen. Then methyl oleate (101 gm) was added. The system was then purged with nitrogen. A low level of vacuum (~600 mm Hg) was developed. Using a syringe, 6.3 gm of a catalyst (tetraisopropyl titanate, Tyzor™ from Dupont) was introduced and the mixture was allowed to agitate for 10 minutes. The temperature was then increased to about 150°C.

During the next 5 hrs, the vacuum was gradually increased to 200 mm Hg. At that point, the reaction was completed and the temperature was reduced to approximately 65°C. Vacuum was broken and 50 gm of water was added to decompose catalyst. The mixture was agitated at 50°C for 1 hr. The pH was adjusted to 6-7 with aqueous oxalic acid and then dried at high vacuum (<5 mm Hg) and 110°C for



- 15 -

0.5 hrs. The product was a brown waxy solid having the following analysis:

<u>Parameter</u>	<u>Value</u>
pH (10% in water)	6.9
Acid Value	0.6
Saponification Value	37.0
Hydroxyl Value	14.0

The mixture was cooled to 80°C as a solution of 566 gm of propylene glycol and 283 gm of water was added with stirring. This mixture was agitated for 0.5 hrs. while allowed to cool. This gave a light brown solution/blend and had a viscosity of about 2000 cP.

### EXAMPLE 3

#### PREPARATION OF PEG-120 METHYL GLUCOSE TRIOLEATE- PG-WATER BLEND

Under a nitrogen atmosphere, a reactor was charged with 42 gm of methyl oleate and 0.8 gm of SAG-10 (anti-foaming agent from Witco Corp., Greenwich, CT). One thousand gm of non-neutralized Glucamate™ DOE-120 was then added. A head-space nitrogen purge was set and the mixture was heated to 175°C. Low vacuum, i.e., about 140 mmHg, was slowly applied when the temperature reached about 150°C.

Once the reaction mixture reached 175°C, the temperature was held there. After about an hour, the head-space purge was switched to a sparge. The vacuum was then slowly increased to about 5 mmHg. The mixture was reacted for an additional 5 hours.

- 16 -

Near the end of the cookout time, a sample was removed for methyl oleate analysis by gas chromatography. The residual methyl oleate decreased to about 0.4% (w/w) and the reaction was cooled to about 80°C, the nitrogen sparge shut off, the vacuum broken with nitrogen, and the product neutralized with an aqueous solution containing 0.6 gm of tartaric acid. The mixture was sampled for pH, color, hydroxyl number, and acid value and viscosity performance. The product, PEG-120 Methyl Glucose Trioleate, analysis showed:

Performance Viscosity*	65,000 cP
Hydroxyl Value	10
GH Color	7
pH (10% in water)	6.5
Acid Value	0.8

To prepare the blend, 1033 gm of propylene glycol (PG) was added to the warm (70-80°C) product, PEG-120 Methyl Glucose Trioleate base prepared above. After the PG was thoroughly mixed in, heating was discontinued, and 517 gm of deionized water was added. The mixture was agitated for about 20 minutes to insure a uniform solution which was then sampled and analyzed for pH, %PG and %water. The product solution was then cooled to about 40°C and stored. The blend had the following analysis:

Water	20%
Propylene glycol	40%
pH (10% solids)	6.5

- 17 -

\* Performance Viscosity method as in Example #4 (Viscosity Measurement)

**EXAMPLE 4**  
**VISCOSITY MEASUREMENT**

Liquid products similar to those prepared in Examples C-1, 2 and 3 were tested in a surfactant-containing liquid to determine the Viscosity Enhancement. The formulation and procedure used were as follows.

<b><u>Ingredients</u></b>	<b><u>wt%</u></b>
Deionized Water	QS to 100
Sodium Laureth Sulfate -2(26 wt% active)	40.00
Cocamidopropyl Betaine (35 wt% active)	11.50
DMDM Hydantoin	0.4
Thickener(40 wt% polyol compound, 40 wt% propylene glycol, 20 wt% water)	1.25

**Procedure:** Add Sodium Laureth Sulfate -2 and Cocamidopropyl Betaine to the water in order, one at a time, until completely uniform before adding the next ingredient. Once uniform add the thickener with stirring and heat to 70°C. Once the thickener is totally dissolved start cooling system to 40°C. At 40°C add DMDM Hydantoin and continue to cool to room temperature. Record viscosity after 24 hours.

The viscosity was measured using a Brookfield RVT Viscometer with a No. 6 spindle at 10 rpm.

- 18 -

<u>Thickener Example</u>	<u>Viscosity, cP</u>	<u>Viscosity Enhancement, %</u>
C-1	13,500	-
2	56,000	315
• 3	65,000	381

**EXAMPLE 5****PREPARATION OF BODY CLEANSING FORMULA**

A body cleansing formula was prepared according to the following composition and procedure.

<u>Ingredients</u>	<u>wt%</u>
Deionized Water	QS
Polyquaternium-10	0.20
Sodium Laureth Sulfate (26wt% active)	40.00
Cocamidopropyl Betaine (35wt% active)	11.50
Disodium Laureth Sulfosuccinate (40wt% active)	5.00
Thickener (40 wt% polyol compound, 40 wt% propylene glycol, 20 wt% water)	0.50
DMDM Hydantoin	0.40

**Procedure:** Add Polyquaternium-10 to room temperature deionized water with adequate agitation. When uniform heat to 70°C and mix until fully hydrated. Once fully hydrated add the remaining ingredients up until DMDM Hydantoin, one at a time in order, waiting until for each to be dissolved before adding the next. Allow to cool to

40°C. At 40°C add DMDM Hydantoin. Continue to cool to room temperature.

The body cleansing formula had a viscosity of 40,500 cP measured using a Brookfield RVT Viscometer with a No. 6 spindle at 10 rpm. Without the thickener, the formula had a viscosity of 3,400 cP.

### **EXAMPLE 6**

#### **COLD PROCESSING**

A liquid product similar to that prepared in Example 2 was tested in a surfactant-containing liquid at ambient temperatures to evaluate cold processing properties. The formulation and procedure used were as follows.

<b><u>Ingredients</u></b>	<b><u>wt%</u></b>
Deionized Water	QS to 100
Sodium Laureth Sulfate -2(26 wt% active)	40.00
Cocamidopropyl Betaine (35 wt% active)	11.50
DMDM Hydantoin	0.4
Thickener(40 wt% polyol compound, 40 wt% propylene glycol, 20 wt% water)	1.25

**Procedure:** The Sodium Laureth Sulfate -2, Cocamidopropyl Betaine and DMDM Hydantoin were added to the water in order, one at a time, until completely uniform before adding the next ingredient. Once uniform, the thickener was added with stirring at ambient temperature and was continued until a thickening response (viscosity increase) was visually observed. The mixing was continued until completely uniform.

Although the invention has been described above with respect to specific aspects, those skilled in the art will recognize that other aspects are intended to be included within the scope of the claims which follow.

We Claim:

1. A composition comprising alkoxyated, glucose derivatives having lipophilic substituents wherein at least 5 wt. % of the glucose derivatives have about three moles of said lipophilic substituents per mole of glucose.
2. The composition of claim 1 comprising an effective amount of glucose derivatives having about three moles of said lipophilic substituents per mole of glucose to provide a Viscosity Enhancement of at least 10%.
3. The composition of claim 1 comprising an effective amount of glucose derivatives having about three moles of said lipophilic substituents per mole of glucose to provide a Viscosity Enhancement of at least 50%.
4. The composition of claim 2 wherein at least 25 wt % of the glucose derivatives have about three moles of said lipophilic substituents per mole of glucose.
5. The composition of claim 1 wherein a portion of the glucose derivatives have one, two or four or more moles of the lipophilic substituents per mole of glucose.
6. The composition of claim 1 wherein the lipophilic substituents are attached to the glucose derivatives by an ester linkage or an ether linkage.

7. The composition of claim 1 wherein the lipophilic substituents have from about 8 to 30 carbon atoms per molecule.

8. The composition of claim 1 wherein the glucose derivatives are substituted with from about 50 to 400 moles of alkylene oxide per mole of glucose.

9. The composition of claim 8 wherein the alkylene oxide is selected from the group consisting of ethylene oxide, propylene oxide and mixtures thereof.

10. The composition of claim 1 wherein the glucose derivative is selected from the group consisting of methyl glucoside, ethyl glucoside, propyl glucoside, butyl glucoside, amyl glucoside and mixtures thereof.

11. The composition of claim 1 which further comprises an alkylene glycol.

12. The composition of claim 11 which is in a liquid form.

13. A process for making alkoxyated, glucose derivatives comprising lipophilic substituents wherein at least 5 wt % of the glucose derivatives have about three moles of said lipophilic substituents per mole of glucose, said process comprising:

- (i) contacting a glucose derivative with an alkylene oxide at reaction conditions effective to form an alkoxyated glucose intermediate substituted with the alkylene oxide; and
- (ii) contacting the alkoxyated glucose intermediate with a lipophilic reagent under reaction conditions effective to form the alkoxyated glucose derivative comprising lipophilic substituents wherein at least 5 wt % of the



glucose derivative has about three moles of said lipophilic substituents per mole of glucose.

14. The process of claim 13 wherein the glucose derivative is partially alkoxyated.

15. The process of claim 13 wherein at least one of step (i) or step (ii) is conducted in the presence of a catalyst selected from the group consisting of acid catalysts, basic catalysts and neutral catalysts.

16. The process of claim 13 wherein the lipophilic reagent is selected from the group consisting of fatty acids, fatty esters, epoxides, halides, glycidyl ethers, vegetable and animal oils and mixtures thereof.

17. A process for making alkoxyated, glucose derivatives comprising lipophilic substituents wherein at least 5 wt % of the glucose derivatives have about three moles of said lipophilic substituents per mole of glucose, said process comprising:

- (i) contacting a glucose derivative with a lipophilic reagent under reaction conditions effective to form a lipophilic glucose intermediate comprising lipophilic substituents wherein at least 5 wt % of the glucose derivative has about three moles of said lipophilic substituent per mole of glucose;
- (ii) contacting the lipophilic glucose intermediate with an alkylene oxide at reaction conditions effective to form the alkoxyated glucose derivative.

18. A process for making alkoxyated, glucose derivatives comprising lipophilic substituents wherein at least 5 wt % of the

- 24 -

glucose derivatives have about three moles of said lipophilic substituents per mole of glucose, said process comprising:

- (i) contacting a glucose derivative with a lipophilic reagent under reaction conditions effective to form a lipophilic glucose intermediate comprising lipophilic substituents wherein at least 75 wt % of the glucose derivative has two moles of said lipophilic substituent per mole of glucose; and
- (ii) contacting the lipophilic glucose intermediate with an alkylene oxide at reaction conditions effective to form an alkoxyated, lipophilic glucose intermediate substituted with the alkylene oxide; and
- (iii) contacting the alkoxyated, lipophilic glucose intermediate with a lipophilic reagent under reaction conditions effective to form the alkoxyated glucose derivative comprising lipophilic substituents wherein at least 5 wt % of the glucose derivative has about three moles of said lipophilic substituent per mole of glucose.

20. A method for thickening a liquid composition comprising a surfactant comprising contacting under mixing conditions one or more alkoxyated, lipophilic polyol compounds with a second liquid comprising a surfactant; characterized in that

- (i) said one or more alkoxyated, lipophilic polyol compounds is present in a liquid form; and
- (ii) a sufficient portion of said one or more alkoxyated, lipophilic polyol compounds are substituted with about three moles of a lipophilic substituent per mole of polyol to provide a Viscosity Enhancement of at least 10%.

21. The method of claim 20 wherein the alkoxyated, lipophilic polyol compound is derived from a polyol selected from the group consisting of glucose, sorbitol, glycerol, polyglycerols and mixtures thereof.

22. The method of claim 20 wherein the Viscosity Enhancement is at least 100%.

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/14072

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 B01F17/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B01F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 687 843 A (MARTIN SMOLIN ET AL) 18 August 1987 (1987-08-18) cited in the application claims 1-38	
A	US 4 450 090 A (JAMES KINNEY) 22 May 1984 (1984-05-22) claims 1-14	

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&amp;" document member of the same patent family

Date of the actual completion of the international search

12 October 1999

Date of mailing of the international search report

21/10/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2.  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Fouquier, J-P

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/14072

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 4687843	A	18-08-1987	CA	1277982 A	18-12-1990
US 4450090	A	22-05-1984	CA	1214394 A	25-11-1986

**THIS PAGE BLANK (USPTO)**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**